

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) A disposable garment comprising:
a front waist region, a back waist region, and a crotch region extending between the waist regions,
a first side panel extending from the front waist region;
a second side panel extending from the back waist region; and
a side seam including a primary bond bonding an inner surface of the first side panel to an inner surface of an edge portion of the second side panel and forming an offset portion at an edge portion of the first side panel, and a secondary bond bonding the offset portion to an outer surface of the second side panel, the secondary bond extending to bond an outer surface of the second side panel edge portion to the outer surface of the second side panel
~~a side seam connecting an edge portion of the first side panel to an edge portion of the second side panel, the first side panel offset with respect to the second side panel,~~

~~wherein the side seam comprises a primary bond and a secondary bond.~~

2. (Canceled)

3. (Withdrawn) The disposable garment of Claim 1 wherein the primary bond connects an outer surface of the first side panel to an outer surface of the second side panel.

4. (Canceled)

5. (Withdrawn) The disposable garment of Claim 1 wherein the secondary bond connects an inner surface of the second side panel to an inner surface of the first side panel.

6. (Withdrawn) The disposable garment of Claim 1 wherein the secondary bond connects an outer surface of the second side panel to an outer surface of the first side panel.

7. (Canceled)

8. (Currently Amended) The disposable garment of Claim 1 wherein the side seam has a width of about ± 5 mm to about 8 mm.

9. (Original) The disposable garment of Claim 1 wherein the primary bond has a width of less than about 30 mm.

10. (Original) The disposable garment of Claim 1 wherein the primary bond has a width of about 2 mm to about 8 mm.

11. (Original) The disposable garment of Claim 1 wherein the secondary bond has a width of less than about 30 mm.

12. (Original) The disposable garment of Claim 1 wherein the secondary bond has a width of about 2 mm to about 8 mm.

13. (Currently Amended) A disposable garment, comprising:
a chassis comprising a front side panel and a back side panel, and
defining a waist opening and first and second leg openings;

a first side seam extending from the waist opening to the first leg opening and connecting the front side panel and the back side panel; ~~the front side panel laterally offset with respect to the back side panel at the first side seam; and~~

a second side seam extending from the waist opening to the second leg opening and connecting the front side panel and the back side panel; ~~the front side panel offset with respect to the back side panel at the second side seam,~~

wherein each side seam having a width of about 5 mm to about 30 mm, and including a primary bond bonding an inner surface of the front side panel to an inner surface of an edge portion of the back side panel and forming an offset portion at an edge portion of the front side panel, and a secondary bond bonding the offset portion to an outer surface of the back side panel, the secondary bond extending to bond an outer surface of the back side panel edge portion to the outer surface of the back side panel comprises a primary bond and a secondary bond.

14. (Canceled)

15. (Canceled)

16. (Withdrawn) The disposable garment of Claim 13 wherein a portion of an inner surface of the front side panel is bonded to a portion of an outer surface of the back side panel.

17. (Currently Amended) A disposable garment comprising:
a front waist region, a back waist region, and a crotch region extending between the waist regions,

a first side panel extending from the front waist region;

a second side panel extending from the back waist region; and

a concealed side seam ~~connecting an edge portion of the first side panel to an edge portion of the second side panel~~ including a primary bond bonding an inner surface of the first side panel to an inner surface of an edge portion of the second side panel and forming an offset portion at an edge portion of the first side panel, and a secondary bond bonding the offset portion to an outer surface of the second side panel, the secondary bond extending to bond an outer surface of the second side panel edge portion to the outer surface of the second side panel, the concealed side seam having a width of about 5 mm to about 30 mm.

18. (Withdrawn) A method for forming a tacked down offset butt side seam comprising:

forming an offset portion by connecting an inner surface of a front side panel to an inner surface of a back side panel using a primary bond, wherein a lateral length of one of the front side panel and back side panel is greater than a lateral length of the other side panel; and

bonding the offset portion to an outer surface of one of the front side panel and the back side panel using a secondary bond.

19. (Withdrawn) The method of Claim 18 wherein the inner surface of the front side panel forming the offset portion is bonded to the outer surface of the back side panel, and the lateral length of the front side panel is greater than the lateral length of the back side panel to form the offset portion.

20. (Withdrawn) The method of Claim 18 wherein the inner surface of the back side panel forming the offset portion is bonded to the outer surface of the front side panel, and the lateral length of the back side panel is greater than the lateral length of the front side panel to form the offset portion.

21. (Withdrawn) The method of Claim 18 wherein the offset portion has a width of about 2 mm to about 30 mm.

22. (Withdrawn) The method of Claim 18 wherein the offset portion has a width of about 3 mm to about 8 mm.

23. (Withdrawn) The method of Claim 18 wherein the offset portion extends along an entire length of the offset butt side seam between a waist opening and a leg opening.

24. (Withdrawn) The method of Claim 18 wherein the inner surface of the front side panel is connected to the inner surface of the back side panel in a close proximity to an outer edge of each side panel.

25. (Withdrawn) The method of Claim 18 wherein a portion of one of the front side panel and the back side panel is cut to form the offset portion.

26. (Withdrawn) The method of Claim 18 wherein the primary bond and the secondary bond each has a width of about 2 mm to about 10 mm.

27. (Withdrawn) The method of Claim 18 wherein an outward edge of the primary bond is about 0 mm to about 15 mm from a distal edge of one of the front side panel and the back side panel.

28. (Withdrawn) A method for forming a folded lap side seam comprising:

forming an overlapped portion by overlapping a front edge portion of a front side panel and a back edge portion of a back side panel, the overlapped portion having a width of about 2 mm to about 30 mm;

bonding the overlapped portion using a primary bond;

folding the back edge portion along a length of an outward edge of the primary bond wherein an outer surface of the back side panel contacts an outer surface of the front side panel;

folding the front edge portion along the length of an inner edge of the primary bond wherein an inner surface of the front side panel contacts an inner surface of the back side panel; and

bonding at least a portion of the folded back edge portion and at least a portion of the folded front edge portion using a secondary bond.

29. (Withdrawn) The method of Claim 28 wherein the overlapped portion has a width of about 4 mm to about 30 mm.

30. (Withdrawn) The method of Claim 28 wherein a distance between a distal edge of the front side panel and the outward edge of the primary bond is about 0 mm to about 12 mm.

31. (Withdrawn) The method of Claim 28 wherein a width of the primary bond is less than the width of the overlapped portion.

32. (Withdrawn) The method of Claim 28 wherein a width of the secondary bond is about equal to a width of the primary bond.

33. (Withdrawn) The method of Claim 28 wherein the overlapped portion extends along an entire length of the folded lap side seam between a waist opening and a leg opening.

34. (Canceled)

Serial No.: 10/027,235

Docket No.: KCC-16,491

Amendment dated 22 January 2005

Reply to Office Action mailed 22 September 2004

35. (Canceled)

36. (Currently Amended) The disposable garment of Claim 13 wherein each side seam has a width of about $2 \leq$ mm to about 8 mm.

37. (Previously Presented) The disposable garment of Claim 13 wherein each primary bond has a width of less than about 30 mm.

38. (Previously Presented) The disposable garment of Claim 13 wherein each primary bond has a width of about 2 mm to about 8 mm.

39. (Previously Presented) The disposable garment of Claim 13 wherein each secondary bond has a width of less than about 30 mm.

40. (Previously Presented) The disposable garment of Claim 13 wherein each secondary bond has a width of about 2 mm to about 8 mm.

41. (Previously Presented) The disposable garment of Claim 13 wherein the front side panel comprises an offset portion having a width in a cross direction of about 2 mm to about 30 mm.

42. (Previously Presented) The disposable garment of Claim 13 wherein the front side panel comprises an offset portion having a width in a cross direction of about 3 mm to about 8 mm.

43. (Currently Amended) The disposable garment of Claim ~~[[14]]~~ 13 wherein an inner surface of an edge portion of the front side panel is bonded to an outer surface of the back side panel.

44. (Canceled)

45. (Currently Amended) The disposable garment of Claim 17 wherein the concealed side seam has a width of about ~~2~~ 5 mm to about 8 mm.

46-48. (Canceled)

49. (Currently Amended) The disposable garment of Claim
[[46]] 17 wherein the primary bond has a width of less than about 30 mm.

50. (Currently Amended) The disposable garment of Claim
[[46]] 17 wherein the primary bond has a width of about 2 mm to about 8 mm.

51. (Currently Amended) The disposable garment of Claim
[[46]] 17 wherein the secondary bond has a width of less than about 30 mm.

52. (Currently Amended) The disposable garment of Claim
[[46]] 17 wherein the secondary bond has a width of about 2 mm to about 8 mm.

53. (New) The disposable garment of Claim 1 wherein the
side seam has a width of about 5 mm to about 30 mm.